



Montgomery County Government
Building and Codes Department

Phone
931-648-5718

350 Pageant Lane Suite 309
Clarksville, TN 37040

Fax
931-553-5121

Montgomery County, TN. Concrete Washout Policy

Montgomery County Storm Water Regulations require all construction and development sites to minimize pollutant releases to the environment to the maximum extent practical by the implementation of accepted Best Management Practices (BMPs) on their sites. **In Montgomery County, all construction and development sites are required to install and properly operate a concrete washout facility.** On individual home building lots that are not part of a larger development, the wash out area cannot be located within 50 feet of storm drains, open ditches, or water bodies.

Concrete washouts are areas used to contain concrete and liquids when the chutes of concrete mixers and hoppers of concrete pumps are rinsed out after use. The washout facilities consolidate solids for easier disposal and prevent runoff of liquid concrete waste.

Concrete wash water is alkaline and is often contaminated by concrete chemical additives like chromium, which can leach into the ground or flow into the storm drain system and contaminate ground and surface water. This contamination causes extreme damage to the environment. Improperly disposal of concrete waste can clog storm drain pipes and cause flooding. Installing concrete washout facilities not only prevents pollution but also is a matter of good housekeeping at your construction site.

Concrete washout facilities cannot be located within 50 feet of storm drains, open ditches, or water bodies. They are to be placed in a location that allows convenient access for concrete trucks, preferably near the area where the concrete is being poured. Appropriate gravel or rock should cover paths to concrete washout facilities if the facilities are located on undeveloped property. These areas should be far enough away from other construction traffic to reduce the likelihood of accidental damage and spills. Only one washout is required for any development.

Washouts should be sized to handle solids, wash water, and rainfall (or should be covered during rain events) and must be large enough to prevent overflow. Concrete Washout Systems, Inc. estimates that 7 gallons of wash water are used to wash one truck chute and 50 gallons are used to wash out the hopper of a concrete pump truck. A good size concrete wash out facility for a large development would be 10 feet long, 15 – 20 feet wide and 2 feet deep. Smaller construction sites can get by with proportionally smaller facilities. For developments, a double plastic liner may be required to prevent contaminant migration. **Do not locate washout facilities within 50 feet of any stream, drainage or storm drain.**

An above-grade washout should be at least ten feet wide by ten feet long and large enough to contain all liquid and solid waste generated in between cleanout periods. The structures can be made from staked straw bales or sandbags, and double lined with heavy gauge plastic sheeting that has no holes or tears. **Do not locate washout facilities within 50 feet of any stream, drainage or storm drain.**

Concrete washouts should be designed to promote evaporation where feasible. If stored liquids have not evaporated and the washout is nearing capacity, dispose of the liquid waste in an approved manner. Remove liquids or cover the structures before predicted rainstorms to prevent overflows. **Do not dispose of the liquids by dumping in or near streams, drainages or storm drains.**

Hardened concrete solids can be broken up and discarded. You can use the solids onsite or haul them away for recycling. Crushed concrete makes excellent aggregate for roadbeds and other building applications.

The Montgomery County Storm Water Program Coordinator can answer any questions about concrete washout facility placement and design. Please feel free to call if you have problems or questions.

More information is available at:

EPA's Office of Ground Water and Drinking Water Web Site:
<http://www.epa.gov/safewater>

Tennessee Department of Environment and Conservation, Office of Water Pollution Control:
<http://tennessee.gov/environment/wpc/>

Montgomery County Storm Water Management and Control Regulation Program Website:
<http://www.montgomerycountyttn.org/county/stormwater/>